



Frame Slider Instructions

ENGINE SLIDERS: KAWASAKI H2 '15-

Left side parts list:

qty 1 L shape slider base bracket
qty 5 m6x70mm socket head bolt
qty 5 35-6 spacer (longer)
qty 1 m6x30mm socket head bolt
qty 1 m6 washer
qty 1 slider

Right side parts list:

qty 1 slider base bracket
qty 3 m6x50mm socket head bolt
qty 2 20-6 spacer; qty 1 18-6 spacer
qty 1 m6x30mm socket head bolt
qty 1 m6 washer
qty 1 slider

Left side:

1. Engine must be cool and safe to touch before installing the engine sliders
2. Place L shape slider base bracket with the center threaded hole in the center upward orientation over the left engine case to identify engine case cover bolts to be removed for the bracket to be mounted over the engine case cover.
3. Remove the engine case cover bolts. Install the base bracket with 35-6 spacers and m6x70mm bolts.
4. Install slider to the base bracket with thread lock, m6x30 bolt and m6 washer.

Right side:

1. Place slider base bracket over the right engine case cover above the small round timing cover to identify the 3 case cover bolts to be removed to mount the bracket. Remove the 3 case cover bolts.
2. Install base bracket with 3 m6x50 bolts, 2 20-6 spacer and 1 18-6 spacer(for the hole on the bracket above the threaded hole)
3. Install slider to the base bracket with thread lock, m6x30 bolt and m6 washer.

****Removable Thread Locking Compound is recommended on all bolt threads****

Tighten all bolts to factory specification. Do not over tighten.

Professional installation is recommended. Always use proper safety measures during the install of this product. Do not try to install this product without proper tools, recently calibrated torque wrench, correct torque specifications from factory service manual, safety goggles and gloves. The motorcycle must be in a fixed secure position before the install process begins. DO NOT remove both engine studs at the same time. PSR frame sliders are meant to help possibly minimize the damages in the event of a crash. PSR do not guarantee the frame sliders will protect your motorcycle from any extent of damage when the bike is dropped or crashed. Customers shall not assume no damages will happen when the frame sliders are installed. PSR is not responsible for any part of your motorcycle for any reason. Precisely measure location of cut and if in doubt at any point please call us before the install process has begun